


92K050 M

9926V2





Features
- Horizontal 13 61/64" Brass arm.
- Arm 1/2" NPT connection.

Material
Solid brass.Finishes resist corrosion and tarnish

Certifications
- ASME A112.18.1/CSA B125.1-12
- California Energy Commission (CEC)
- ADA

- Available color finishes
 10 chrome
 34 matt copper.
 35 brushed dark nickel.
 38 matt black.
 43 matt white.
 44 brushed steel finish.
 50 bronze.
 53 gold.
 68 polish nickel. 34 matt coppe

Technical information

All product dimensions are nominal.

Wall-mounted.

Max flow rate: 2 gpm.

Warranty
Limited warranty.
See website for detailed warranty information.

Note
Install this product according to the installation guide.
In a measurements confirm with product
Palazzani reserves the right to make revisions without notice to product specifications.

code **9926A7**





Features

· Horizontal 13 61/64" Brass arm.

· Arm 1/2" NPT connection.

Material
Solid brass.
Finishes resist corrosion and tarnish

Certifications
- ASME A112.18.1/CSA B125.1-12
- California Energy Commission (CEC)
- ADA

Available color finishes
1 0 chrome
34 matt copper.
36 brushed dark nickel.
38 matt black.
43 matt white.
49 brushed steel finish.
50 bronze.
53 gold.
68 pollish nickel. 34 matt copper.


Technical information
All product dimensions are nominal.
Wall-mounted.
Max flow rate: 2 gpm.

Warranty
- Limited warranty.
- See website for detailed warranty information.

Note
-Install this product according to the installation guide.
-Final measurements confirm with product
-Palazzani reserves the right to make revisions without notice to product specifications.

code 992774 + 562503





Features

Themostatich volume and temperature control pressure balance 2 ways complete with concealed parts.

Temperature memory allows faucet to be turned on and off at any temperature setting.

Safety stop at 38°.

Sult in non-teturn valve.

Ceramic disc valves longevity standards for a lifetime of durable performance.

Valve body cast brass.

Material
Solid brass.
Finishes resist corrosion and tarnish

Certifications
- ASME A112.18.1/CSA B125.1-12
- California Energy Commission (CEC)
- ADA


Available color finishes · 10 chrome

Technical information
- All product dimensions are nominal
- Handle clearance 1-31/32" (50mm)
- Faucet flow rate: 7.5 gpm
- Pressure 60 psi

Note
-Install this product according to the installation guide.
-Final measurements confirm with product.
-Palazzani reserves the right to make revisions without notice to product specifications.

code **991023**





Features
- Fixed bracket in brass with water delivery.
- Flexible tube 4 11 1/16".
- Handshower in abs at 3/32".
- Easy-clean system.
- Coated with 20 micron of chrome.

Material
Solid brass.
ABS.
Finishes resist corrosion and tarnish.

Certifications · ADA

Available color finishes · 10 chrome

Technical information

All product dimensions are nomin

Max flow rate: 2 gpm.

Wall-mount. Pressure: 45 psi.

Note
-Install this product according to the installation guide.
-Final measurements confirm with product.
-Palazzani reserves the right to make revisions without notice to product specifications.

